Antelco Group of Companies

LINCOLN Est. 1959 MOULDING THE FUTURE · ANTELCO® · Dawn®

Putting Water Where it Counts!®





Antelco Australia
Antelco Pty Ltd ABN 50 008 062 708
Sales & Marketing,
Orders & Warehouse
Research & Development
PO Box 95, 131 Tolley Rd,
St Agnes SA 5097 Australia
+61 8 8334 4333
adelaide@antelco.com.au

Antelco USA
Antelco Corporation
Sales & Marketing,
Orders & Warehouse
886 Waterway Pl,
Longwood,
Florida 32750 USA
+1 407 331 0699
info@antelco.com

Antelco Europe
Antelco UK Limited
Sales & Marketing,
Orders & Warehouse
17a Chartmoor Rd,
Leighton Buzzard,
Bedfordshire LU7 4WG UK
+44 152 585 9990
orders@antelco.co.uk

CFd™ DownSpray

antelco.com

CFd™ DownSpray

The patented CFd™ DownSpray is a 360º spray jet that distributes water evenly across the wetted surface area. Stake assembly options provide savings in labor and installation time.

Features

- 45º downspray reduces the effect of wind.
- Gentle spray pattern minimizes damage to delicate plant foliage.
- 45° downspray pattern gives consistent pattern diameter with different inlet pressures making CFd™ ideal for pot watering.
- Six color coded frames to identify flow rates.
- "Quick" thread for easy insertion into tubing.
- Galvanized wire stake assembly with 36" tubing incorporates shut-off clip to stop flow.
- Patented (US patent 8480013) design provides uniform water application.
- UV stabilized materials for long life.
- Diameter of spray pattern can be easily adjusted by raising or lowering the emitter height.
- Stake assemblies includes self piercing adapter for easy installation into lateral tubing.

NEW



Scan to see how it works

Applications

Nurseries, tree lots, pot plants, home and landscaped gardens.



CFd™ DownSpray Wire Stake Assembly with flow shut-off

Performance Chart

Pattern	360º		
	Tested at 10" above ground level		
Nozzle Size & Color	Pressure (psi)	Flow (gph)	Diameter (in)
0.030" Black	10	4.9	24
	15	6.0	24
	20	7.0	22
	25	7.8	20
0.035" Brown	10	6.2	24
	15	7.6	22
	20	8.7	20
	25	9.8	20
0.040" Blue	10	7.3	24
	15	8.9	22
	20	10.2	20
	25	11.5	20
0.045" Gray	10	9.6	24
	15	11.8	24
	20	13.7	20
	25	15.3	20
0.060" Red	10	15.8	24
	15	19.6	24
	20	22.7	20
	25	25.5	20
0.082" Purple	10	29.6	24
	15	36.4	24
	20	42.4	20
	25	47.3	20

Ordering Information - CFd™ DownSpray

Nozzle Size & Color	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
0.030" Black	19005	100	50	18.1
0.035" Brown	19025	100	50	18.1
0.040" Blue	19015	100	50	18.1
0.045" Gray	19045	100	50	18.1
0.060" Red	19055	100	50	18.1
0.082" Purple	19065	100	50	18.1

Ordering Information - CFd™ Galvanized Wire Stake Assembly w/Shut-Off Clip

Nozzle Size & Color	Tube Length	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
0.030" Black	36"	54305	25	12	20.1
0.035" Brown	36"	54325	25	12	20.1
0.040" Blue	36"	54315	25	12	20.1
0.045" Gray	36"	54405	25	12	20.1
0.060" Red	36"	54415	25	12	20.1
0.082" Purple	36"	54425	25	12	20.1





CFd™ DownSpray Range